




TRIAX

connecting the future



1080p and 4K Point to Point Kits

For an enhanced viewing experience at a second TV location

TRIAX PtP 1080p kit offers a cost effective solution to extend 1080p Full HD HDMI signals to a second TV location without additional subscriptions.

The PtP 4K Kit enables a further viewing experience up to 4K Ultra HD.

For both models the signal is passed between a transmitter and receiver over CAT 5/6 cable.

310072 PtP1080p Kit
310073 PtP 4K Kit



triax.uk/in-house-connectivity



TRIAx

connecting the future

PtP 1080p Kit

- Supports HDMI 1.3, HDCP 1.4 compliant
- Supports built-in EDID to ensure HDMI signals transmission from source to display
- Transmission of 1080p@60Hz (max) signals up to 55m including embedded multi-channel audio
- Supports bi-directional IR pass-through
- Supports PoC (the Receiver can be powered via Transmitter)

PtP 4K Kit

- HDMI 2.0 standard and HDCP 2.2 compliant
- Supports video resolution up to 4Kx2K@60Hz 4:4:4
- Transmission distance is up to 131ft/40m for 4Kx2K, and 230ft/70m for 1080P
- Supports bi-directional IR pass-through for long-distance control
- Supports bi-directional 24V PoC
- Supports CEC
- Visually Lossless Compression (VLC) technology

Model	PtP 1080p		PtP 4k	
Part No.	310072		310073	
	Transmitter	Receiver	Transmitter	Receiver
Input	(1) HDMI	(1) CAT	(1) HDMI	(1) HDBT
Input Connector	(1) 19-pin type-A female HDMI	(1) RJ45	(1) Female type-A HDMI	(1) RJ45
Output	(1) HDMI; (1) CAT	(1) HDMI	(1) HDBT	(1) HDMI
Output Connector	(1) 19-pin type-A female HDMI; (1) RJ45	(1) 19-pin type-A female HDMI	(1) RJ45	(1) Female type-A HDMI
Control	(1) IR IN; (1) IR OUT	(1) IR IN; (1) IR OUT	(1) IR IN; (1) IR OUT	(1) IR IN; (1) IR OUT
Control Connector	(2) 3.5mm mini jacks	(2) 3.5mm mini jacks	(2) 3.5mm mini jacks	(2) 3.5mm mini jacks
Transmission Distance	1080p@60Hz≤55m		1080P@60Hz ≤ 230ft/70m, 4K@60Hz ≤131ft/40m	
HDMI Standard	1.3		2.0	
HDCP Version	1.4		2.2	
Bandwidth	-		18 Gbps	
Power Supply	Input: 100VAC~240VAC, 50/60Hz; Output: 5VDC 1A		Input Power: 24V DC 1.25A or Power over Cable (PoC), AC Adaptor Input Power: 100~240VAC, 50/60Hz	
Power Consumption	4W (Max)		9.5W (Max)	
Operating Temperature	-10~55°C		-10~55°C	
Dimensions (W*H*D)	66 x 16.8 x 66.0mm	66 x 16.8 x 66.0mm	61 x 24 x 120mm	61 x 24 x 120mm
Weight	36 g	38 g	560 g / Set	
Contents	1 x PtP 1080p Transmitter, 1 x Receiver, 1 x Power Adaptor, 1 x IR Receiver, 1 x IR Emitter, 1 x User manual		1 x PtP 4K Transmitter, 1 x Receiver, 1 x Power Adaptor, 1 x IR Receiver, 1 x IR Emitter, 1 x User manual	

