



Introducing the NEW KM range of masthead amplifiers.

Kingray are proud to introduce the latest Australian designed amplifier range. The use of Advanced Surface Mount Technology and mechanical design offers renowned Kingray quality and value in a compact housing.

Note: The KMD24FS input filtering rejects band 1, to optimise digital reception.

Features

- > Amplifies both analogue and digital signals
- > Combined or separate antenna inputs
- > Adjustable gain controls
- > Shielded case
- > F type connections
- > Weather resistant housing
- > Packed with a PSK08 power supply
- > 3 year warranty
- > Includes adjustment tool
- > All models available in Trade Packs (Quantity 5)



TRADE PACK
includes power supplies



	KMW32FS	KMD24FS	KMU32FS
Frequency range	VHF 44 - 230 MHz UHF 520 - 820 MHz	VHF 174 - 230 MHz UHF 520 - 820 MHz	VHF 44 - 230 MHz UHF 520 - 820 MHz
Max. gain	VHF 26 dB UHF 32 dB	VHF 15 dB UHF 24 dB	VHF -2 dB UHF 32 dB
Gain control	VHF 10 dB UHF 10 dB	VHF 10 dB UHF 10 dB	VHF n/a UHF 10 dB
Noise figure	VHF < 3 dB UHF < 2.5 dB	VHF < 3 dB UHF < 2.5 dB	VHF < 3 dB UHF < 2.5 dB
Max. output	108 dB @ -60 dB IMR (DIN45004B)	108 dB @ -60 dB IMR (DIN45004B)	108 dB @ -60 dB IMR (DIN45004B)

