

digi-MOD[®]HD

Quad Input High Definition DVB-T Modulator

RL-HD4002DM



FEATURES

- Quad Input High Definition DVB-T Modulator that converts HD video and audio signals to digital COFDM DVB-T Channel
- Dual Mode - MPEG-2 & H.264 (MPEG-4) Encoding
- Distributes 576i / 720P / 1080i / 1080P picture quality (1080P only available on H.264)
- HDMI, Component, CVBS & Analogue Audio Inputs
- Programmable; Channel, Network Names and LCN
- Full function front LCD display for adjustments
- Remote Access and control GUI via Web browser
- Internal FAN Cooling System for Long Life Span
- 2K/8K Carriers
- Adjustable VHF / UHF Output (6-69)
- 20 dB Adjustable Attenuation (100dB launch)
- 1 RU Rack Mountable
- Distributes on any new or existing RF cable
- Installed within minutes – plug n play technology

SPECIFICATIONS

Number of Inputs	4
Video Encoding	MPEG - 2 / H.264 (MPEG -4)
Channel Output	6 - 69
Output Connector	F type
Video Input	HDMI / Component / CVBSv
Audio Input	HDMI / Analogue Stereo
Video Resolution	576i / 720P / 1080i / 1080P
Output Level	100dBuV
Output Level Adjustment	20 dB typ.