

Taps



Penta Tap®



Twin Penta Tap®

**AZR 5550 / 10 F, AZR 5550 / 15 F
AZR 5550 / 20 F AZR 55250 / 10 F**

- The installation expenditure of major distribution networks can be reduced substantially.
- Easy installation, just one device instead of five.
- The trunk line DC-path is also linked to the tap outlets. This offers remote power to post amplifiers in tap lines.

Model Art. No.		AZR 5550 / 10 F 841113	AZR 5550 / 15 F 841114	AZR 5550 / 20 F 841115	AZR 55250 / 10 F 841151
EAN		4040326411131	4040326411148	4040326411155	4040326411513
Inputs SAT / terrestrial		4 / 1			
Outputs SAT / terrestrial		4 / 1 + 4 / 1			4 / 1 + 4 / 1 + 4 / 1
Frequency range		5 ... 862 MHz 4 x 950 ... 2200 MHz			
Tap loss Tap 1 terrestrial SAT		10 dB 13 ... 10 dB	16 dB 19 ... 15 dB	17 dB 24 ... 20 dB	10 dB 14 ... 10 dB
Tap loss Tap 2 terrestrial SAT		-	-	-	10 dB 14 ... 10 dB
Through loss trunk terrestrial SAT		2,5 ... 2 dB 1 ... 2 dB	1 ... 2 dB 1 ... 2 dB	1 ... 1,5 dB 1 ... 2 dB	4 ... 5 dB 1,5 ... 3 dB
Isolation	Trunk / trunk	typ. 26 dB			
	Trunk / tap	typ. 26 dB			
	Tap / tap	typ. 26 dB			
DC-pass max.		30V / 1 A			
Ambient temperature		-20 ... +50 °C			
Dimensions (mm)		145 x 130 x 39			