

Cascadable Multiswitch 2 in 12



SMS 2212 F

For 12 subscribers.

- Remote powered by satellite receiver.
- The IF polarity selection is controlled by the remote voltage, $< 14V \cong \text{Vert.} / > 16V \cong \text{Hor.}$ provided by the receiver.

Model Art. No.	SMS 2212 F 842344
EAN	4040326423448
Inputs/outputs	2/2
Subscriber outputs	12
Through loss SAT IF 950...2200 MHz	0 dB
Tap loss SAT	0 dB
Output level max. 950...2150 MHz 35 dB IMA ₃ /EN 60728-3	94 dB μ V
Isolation receiver/receiver	typ. 23 dB
Isolation trunk/trunk	typ. 30 dB
Current consumption	75 mA
Capacity (IF ports) max.	500 mA
Ambient temperature	-20...+50 °C
Dimensions (mm)	205 x 90 x 40

Compact Multiswitch 2 in 8



SMS 287 F

For 8 subscribers.

- Remote powered by satellite receiver.
 - Compact multiswitch for distribution of 2 SAT IF signals for 8 subscribers.
- The IF polarity selection is controlled by the remote voltage, $< 14V \cong \text{Vert.} / > 16V \cong \text{Hor.}$ provided by the receiver.

Model Art. No.	SMS 287 F 842497
EAN	4040326424971
Inputs	2
Subscriber outputs	8
Through gain SAT IF 950...2200 MHz	0...3,5 dB
Output level max. 950...2150 MHz 35 dB IMA ₃ /EN 60728-3	98 dB μ V
Isolation receiver/receiver	typ. 26 dB
Current consumption	-
Current consumption from each receiver	75 mA
Current (IF ports) max.	500 mA
Ambient temperature	-20...+50 °C
Dimensions (mm)	140 x 90 x 40