




COMMERCIAL

TAPS

TAP 4 WAY F TYPE 12 dB 5 ... 1000 MHz

Product Code: AS4TF12

FOXTEL: F30253



- Suitable for CATV, SMATV, MATV and FTA

Specifications	Frequency (MHz)	AS4TF12
Insertion loss IN-OUT (dB)	5-40	≤ 5.0
	40-470	≤ 5.0
	470-862	≤ 5.5
	862-1000	≤ 6.0
Tap loss IN-TAP (dB)	5-40	14 ± 2.5
	40 - 1000	14 ± 2.0
	1000 - 1750	14 ± 2.0
	1750 - 2150	14 ± 2.5
Isolation TAP-TAP (dB)	5-40	≤ 40
	40 - 1000	≤ 32
	1000 - 1750	≤ 28
	1750 - 2150	≤ 25
Isolation OUT-TAP (dB)	5-40	≤ 25
	40 - 1000	≤ 20
	1000 - 1750	≤ 20
	1750 - 2150	≤ 20
Return Loss OUT (dB)	5-40	≤ 8
	40 - 1000	≤ 10
	1000 - 1750	≤ 10
	1750 - 2150	≤ 10
Impedance		75 Ω
Housing	Zinc Die Cast, Stannum-plated, Bright Tin Finish & Solder Shielded Bottom Plate	
Wall Mounting Screws	$\pm$ PM 4 x 18 A3 Nickel-Plated, 2 pcs	
Power Pass	Input > Output, Max: DC 30 V @ 1 A	
Earthing Terminal	Yes	